

SPECIFICATION

Moonstone

LED Panel (1200 x 600mm)



Beam Angle
120°



Input
220-240V



Life Hours
30,000



Dimmable
Available



Colour Temperature
4000K

Part Number	MS5-126N
Wattage	60W
Input Voltage	220-240V
Beam Angle	120°
Life Expectancy	30,000
Case	PMMA & Aluminium Trim
Colour Temperature	4000K
Output Lumens	7200lm
Dimmable	No
Switch Time	15,000
Instant Light	Yes
CRI	>80
IP Rating	IP20
IK Rating	IK05
Dimensions (mm)	1195 x 595 x 7.5
Surface Mount Kit	MS5-CWM126

Key Features

- Suspension Kit part number: **MS5-SUS**
- 3000K & 5750K options
- Available with a range of sensor options: Emergency, Microwave, Daylight Harvesting
- RGB panels also available
- Panel available to meet UGR19 lighting schemes
- 5 year warranty



Please Note: Product specifications are subject to change without notice. Product supplied may differ slightly in appearance from images shown on this website. Diamond LED Lighting reserve the right to update product specifications.

Tel: 01260 292 640 | Fax: 01260 279 116 | E-mail: sales@diamondledlighting.co.uk | Web: www.diamondledlighting.co.uk